



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	40 L/min.
Maximum Operating Pressure	350 bar
Check Cracking Pressure	1,7 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at Reseat	0,3 cc/min.
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	6
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.20 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

OPTION SELECTION EXAMPLE: HRDALAN

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
L Standard Screw Adjustment	A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	Standard Material/Coating
C Tamper Resistant - Factory Set	D 200 - 700 psi (14 - 50 bar), 400 psi (28 bar) Standard Setting	V Viton	/AP Stainless Steel, Passivated
	W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting		

PERFORMANCE CURVES

