



2

3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-21A
	1
	40 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min.@70 bar
	1,7 bar
	15 L/min.
	10 ms
	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.19 kg.
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

OPTION SELECTION EXAMPLE: HVCALAN

(L)

(A)

(N)

L	A	N
C -	75 - 3000 psi (5 - 210 bar), 1000 psi (70 bar)	N
K	B 75 - 1500 psi (5 - 105 bar), 1000 psi (70 bar)	V
	D 75 - 800 psi (5 - 55 bar), 400 psi (28 bar)	
	W 75 - 4500 psi (5 - 315 bar), 1000 psi (70 bar)	

TECHNICAL FEATURES

- Sun
- 75 psi (5 bar)
- 3 1:1
- 1 / 0,07 cc/min
- 4
- Sun /

PERFORMANCE CURVES

