



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min. @70 bar
Pilot Passage into Valve	0,8 mm
Pilot Volume Displacement	0,33 cc
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

**CONFIGURATION OPTIONS**

Model Code Example: **LKDCXN**

CONTROL	(X)
<b>X</b> Not Adjustable	
<b>K</b> manilla	
<b>L</b> activador manual	
<b>P</b> External 1/4 NPTF Pilot Port, Port 3 Blocked	

SEAL MATERIAL	(N)
<b>N</b> Buna-N	
<b>V</b> Viton	

MATERIAL/COATING	(N)
<b>Standard Material/Coating</b>	
<b>/AP</b> Stainless Steel, Passivated	
<b>/LH</b> Mild Steel, Zinc-Nickel	