



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|   |                           |
|---|---------------------------|
| cavidad                                   | T-11A                     |
| Series                                    | 1                         |
| Capacity                                  | 60 L/min.                 |
| Maximum Operating Pressure                | 350 bar                   |
| Area Ratio, A3 to A1                      | 1.8:1                     |
| Area Ratio, A3 to A2                      | 2.25:1                    |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,7 cc/min.@70 bar        |
| Pilot Passage into Valve                  | 0,8 mm                    |
| Pilot Volume Displacement                 | 0,33 cc                   |
| Valve Hex Size                            | 22,2 mm                   |
| Valve Installation Torque                 | 41 - 47 Nm                |
| Seal kit - Cartridge                      | Buna: 990-011-007         |
| Seal kit - Cartridge                      | Polyurethane: 990-011-002 |
| Seal kit - Cartridge                      | Viton: 990-011-006        |
| Seal kit - Cartridge                      | Buna: 990-011-007         |
| Seal kit - Cartridge                      | Polyurethane: 990-011-002 |
| Seal kit - Cartridge                      | Viton: 990-011-006        |

## OPTION SELECTION EXAMPLE: LKDCXN

**CONTROL**

(X)

**SEAL MATERIAL**

(N)

**MATERIAL/COATING**

- X** Not Adjustable
- K** manilla
- L** activador manual
- P** External 1/4 NPTF Pilot Port, Port 3 Blocked

- N** Buna-N
- V** Viton

- Standard Material/Coating**
- /AP** Stainless Steel, Passivated
- /LH** Mild Steel, Zinc-Nickel

**PERFORMANCE CURVES**

