



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@70 bar
Pilot Passage into Valve	0,9 mm
Pilot Volume Displacement	0,98 cc
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

CONFIGURATION OPTIONS

Model Code Example: **LKFCXN**

CONTROL

(X)

SEAL MATERIAL

(N)

MATERIAL/COATING

- X** Not Adjustable
- L** activador manual
- P** External 1/4 NPTF Pilot Port, Port 3 Blocked

- N** Buna-N
- E** EPDM
- V** Viton

- Standard Material/Coating**
- /AP** Stainless Steel, Passivated
- /LH** Mild Steel, Zinc-Nickel