



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---|---------------------------|
| cavidad | T-11A |
| Series | 1 |
| Capacity | 95 L/min. |
| Maximum Operating Pressure | 350 bar |
| Area Ratio, A3 to A1 | 1.8:1 |
| Area Ratio, A3 to A2 | 2.25:1 |
| Control Orifice Diameter | 0,53 mm |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,7 cc/min. |
| Pilot Volume Displacement | 0,66 cc |
| Valve Hex Size | 22,2 mm |
| Valve Installation Torque | 41 - 47 Nm |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |

OPTION SELECTION EXAMPLE: LODAXN

CONTROL

- Not Adjustable
- Stroke Adjustment

(X) SEAL MATERIAL

- Buna-N
- Viton

(N) MATERIAL/COATING

- Standard Material/Coating
- IAP Stainless Steel, Passivated

PERFORMANCE CURVES

