



These unbalanced, pilot-to-close logic valves are 2-way switching elements that are spring biased closed. Pressure at either work port 1 or 2 will oppose the spring and tend to open the valve while pressure at port 3 will tend to close it. The force generated at port 3, plus the spring force, must be greater than the sum of the forces acting at port 1 and port 2 for the valve to remain closed. NOTE: The pilot area (port 3) is 1.8 times the area at port 1 and 2.25 times the area at port 2.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Maximum Valve Leakage at 110 SUS (24 cSt)	10 drops/min.
Pilot Passage into Valve	.031 in.
Pilot Volume Displacement	.04 in <sup>3</sup>
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

**CONFIGURATION OPTIONS**

Model Code Example: **LODCLXN**

**CONTROL**

(L)

**SEAL MATERIAL**

(N)

**MATERIAL/COATING**

**L** Stroke Adjustment

**N** Buna-N

Standard Material/Coating

**K** Handknob

**V** Viton

**/AP** Stainless Steel, Passivated

**X** Not Adjustable

**/LH** Mild Steel, Zinc-Nickel