



CONFIGURATION

X Control	Not Adjustable
Cracking Pressure	
Seal Material	
Material/Coating	

TECHNICAL DATA

NOTE:

cavidad	T-11A	DATA
Series	1	MAY
Capacity	95 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Area Ratio, A3 to A1	1.8:1	
Area Ratio, A3 to A2	2.25:1	
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.	
Pilot Passage into Valve	0,8 mm	
Pilot Volume Displacement	0,66 cc	
Valve Hex Size	22,2 mm	
Valve Installation Torque	41 - 47 Nm	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: LODCXN

CONTROL	(X) CRACKING PRESSURE	(D) SEAL MATERIAL	(V) MATERIAL/COATING
X Not Adjustable	D 50 psi (3,5 bar)	V Viton N Buna-N	/LH Mild Steel, Zinc-Nickel /AP Stainless Steel, Passivated Standard Material/Coating

PERFORMANCE CURVES

