



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	95 L/min.
Maximum Operating Pressure	350 bar
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Control Orifice Diameter	0,53 mm
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.
Pilot Volume Displacement	0,66 cc
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

## OPTION SELECTION EXAMPLE: LODDXN

**CONTROL**

(X)

**SEAL MATERIAL**

(N)

**MATERIAL/COATING**

**X** Not Adjustable  
**L** Stroke Adjustment

**N** Buna-N  
**E** EPDM  
**V** Viton

Standard Material/Coating  
**/AP** Stainless Steel, Passivated

### PERFORMANCE CURVES

