



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	95 L/min.
Maximum Operating Pressure	350 bar
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Control Orifice Diameter	0,53 mm
Pilot Control Cavity	T-8A
Pilot Volume Displacement	0,66 cc
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

# OPTION SELECTION EXAMPLE: LODD8DN

CRACKING PRESSURE

(D)

SEAL MATERIAL

(N)

MATERIAL/COATING

D 50 psi (3,5 bar)

N Buna-N

Standard Material/Coating

E EPDM

/AP Stainless Steel, Passivated

V Viton

## PERFORMANCE CURVES

