



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                            |                           |
|----------------------------|---------------------------|
| cavidad                    | T-11A                     |
| Series                     | 1                         |
| Capacity                   | 95 L/min.                 |
| Maximum Operating Pressure | 350 bar                   |
| Area Ratio, A3 to A1       | 1.8:1                     |
| Area Ratio, A3 to A2       | 2.25:1                    |
| Control Orifice Diameter   | 0,53 mm                   |
| Pilot Control Cavity       | T-8A                      |
| Pilot Volume Displacement  | 0,66 cc                   |
| Valve Hex Size             | 22,2 mm                   |
| Valve Installation Torque  | 41 - 47 Nm                |
| Seal kit - Cartridge       | Buna: 990-011-007         |
| Seal kit - Cartridge       | EPDM: 990-011-014         |
| Seal kit - Cartridge       | Polyurethane: 990-011-002 |
| Seal kit - Cartridge       | Viton: 990-011-006        |

# OPTION SELECTION EXAMPLE: LODD8N

## SEAL MATERIAL

## (N) MATERIAL/COATING

N Buna-N

Standard Material/Coating

E EPDM

IAP Stainless Steel, Passivated

V Viton

## PERFORMANCE CURVES

