



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.
Pilot Passage into Valve	0,9 mm
Pilot Volume Displacement	1,1 cc
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

**CONFIGURATION OPTIONS**

Model Code Example: **LOFCXN**

**CONTROL**

(X)

**SEAL MATERIAL**

(N)

**MATERIAL/COATING**

**X** piloto estándar

**L** Stroke Adjustment

**P** External 1/4 NPTF Pilot Port, Port 3 Blocked

**N** Buna-N

**E** EPDM

**V** Viton

Standard Material/Coating

**/AP** Stainless Steel, Passivated

**/LH** Mild Steel, Zinc-Nickel