



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-2A
Series	2
Capacity	200 L/min.
Maximum Operating Pressure	350 bar
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.
Pilot Passage into Valve	0,9 mm
Pilot Volume Displacement	1,1 cc
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

## OPTION SELECTION EXAMPLE: LOFCXN

**CONTROL**

(X)

**SEAL MATERIAL**

(N)

**MATERIAL/COATING**

- X** piloto estándar
- L** Stroke Adjustment
- P** External 1/4 NPTF Pilot Port, Port 3 Blocked

- N** Buna-N
- E** EPDM
- V** Viton

- Standard Material/Coating**
- /AP** Stainless Steel, Passivated
- /LH** Mild Steel, Zinc-Nickel

**PERFORMANCE CURVES**

