



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-17A
Series	3
Capacity	380 L/min.
Maximum Operating Pressure	350 bar
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Control Orifice Diameter	0,8 mm
Pilot Volume Displacement	4,1 cc
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

OPTION SELECTION EXAMPLE: LOHAXN

CONTROL

- X** Not Adjustable
- L Stroke Adjustment
- P External 1/4 NPTF Port, Port 3 blocked

(X) SEAL MATERIAL

- N** Buna-N
- V Viton

(N) MATERIAL/COATING

- Standard Material/Coating
- /AP** Stainless Steel, Passivated

PERFORMANCE CURVES

