



CONFIGURATION

Cracking Pressure

Seal Material

Material/Coating

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---|---------------------------|
| cavidad | T-17A |
| Series | 3 |
| Capacity | 380 L/min. |
| Maximum Operating Pressure | 350 bar |
| Area Ratio, A3 to A1 | 1.8:1 |
| Area Ratio, A3 to A2 | 2.25:1 |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,7 cc/min. |
| Pilot Volume Displacement | 4,1 cc |
| Valve Hex Size | 31,8 mm |
| Valve Installation Torque | 203 - 217 Nm |
| Model Weight | 0,55 kg |
| Seal kit - Cartridge | Buna: 990-017-007 |
| Seal kit - Cartridge | EPDM: 990-017-014 |
| Seal kit - Cartridge | Polyurethane: 990-017-002 |
| Seal kit - Cartridge | Viton: 990-017-006 |
| Seal kit - Cartridge | Buna: 990-017-007 |
| Seal kit - Cartridge | EPDM: 990-017-014 |
| Seal kit - Cartridge | Polyurethane: 990-017-002 |
| Seal kit - Cartridge | Viton: 990-017-006 |

OPTION SELECTION EXAMPLE: LOHCLN

CRACKING PRESSURE

(D)

SEAL MATERIAL

(N)

MATERIAL/COATING

(/LH)

D 50 psi (3,5 bar)

N Buna-N

/LH Mild Steel, Zinc-Nickel

E EPDM

/AP Stainless Steel, Passivated

V Viton

Standard Material/Coating

PERFORMANCE CURVES

