



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.
Pilot Passage into Valve	1,50 mm
Pilot Volume Displacement	4,1 cc
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

**CONFIGURATION OPTIONS**

Model Code Example: **LOHOXN**

CONTROL

(X)

SEAL MATERIAL

(N)

MATERIAL/COATING

**X** Not Adjustable

**N** Buna-N

Standard Material/Coating

**E** EPDM

**/AP** Stainless Steel, Passivated

**V** Viton