



This valve is an unbalanced, vent-to-open 2-way logic switching element with an integral pilot control cavity. It is spring biased closed and incorporates an integral shuttle so that the higher of pressures at either port 1 or port 2 can be used as a pilot source. With a pilot 2-way valve in the closed position installed in the T-8A cavity, the logic element will remain in the closed position. With the pilot valve open, the logic element will open providing there is a sufficient combination of pressures to overcome the spring force. The force generated at port 3, plus the spring force, must be greater than the sum of the forces acting at port 1 and port 2 for the valve to remain closed. NOTE: The pilot area (port 3) is 1.8 times the area at port 1 and 2.25 times the area at port 2.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Control Orifice Diameter	.035 in.
Pilot Control Cavity	T-8A
Pilot Volume Displacement	.42 in ³
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

NOTES: • Compound cartridge (pilot and main stage) assembly information is provided for reference only. Cartridges must be ordered separately and assembled at point of use.

CONFIGURATION OPTIONS

Model Code Example: **LOJD8DN**

CRACKING PRESSURE

(D) SEAL MATERIAL

(N) MATERIAL/COATING

D 50 psi (3,5 bar)

N Buna-N

Standard Material/Coating

V Viton

/LH Mild Steel, Zinc-Nickel