

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-19AU
Series	4
Capacity	1100 L/min.
Maximum Operating Pressure	350 bar
Area Ratio, A3 to A1	1.8:1
Area Ratio, A3 to A2	2.25:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.
Pilot Passage into Valve	2,3 mm
Pilot Volume Displacement	7,7 cc
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	EPDM: 990-019-014
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	EPDM: 990-019-014
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

OPTION SELECTION EXAMPLE: LOKCXN

CONTROL

X Not Adjustable

(X) **SEAL MATERIAL**


N Buna-N
E EPDM
V Viton

(N) **MATERIAL/COATING**

Standard Material/Coating
/AP Stainless Steel, Passivated
/LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

Model LOKC installed in T-19AU Cavity



Model LOKC installed in T-19A Cavity

