



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---|---------------------------|
| Maximum Operating Pressure | 350 bar |
| Area Ratio, A3 to A1 | 1.8:1 |
| Area Ratio, A3 to A2 | 2.25:1 |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,7 cc/min. |
| Pilot Passage into Valve | 2,3 mm |
| Pilot Volume Displacement | 7,7 cc |
| Seal kit - Cartridge | Buna: 990-019-007 |
| Seal kit - Cartridge | Polyurethane: 990-019-002 |
| Seal kit - Cartridge | Viton: 990-019-006 |
| Seal kit - Cartridge | Buna: 990-019-007 |
| Seal kit - Cartridge | Polyurethane: 990-019-002 |
| Seal kit - Cartridge | Viton: 990-019-006 |

CONFIGURATION OPTIONS

Model Code Example: LOKOXN

CONTROL

(X)

SEAL MATERIAL

(N)

MATERIAL/COATING

X Not Adjustable

N Buna-N

Standard Material/Coating

P External 1/4 NPTF Pilot Port, Port 3 Blocked

E EPDM

/AP Stainless Steel, Passivated

V Viton