



Normally open modulating elements without an internal orifice act as a restrictive compensator to maintain a constant pressure drop across an orifice, regardless of variations in upstream or downstream pressure.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------------|---------------------------|
| Cavity | T-2A |
| Series | 2 |
| Capacity | 30 gpm |
| Maximum Operating Pressure | 5000 psi |
| Valve Hex Size | 1 1/8 in. |
| Valve Installation Torque | 45 - 50 lbf ft |
| Seal kit - Cartridge | Buna: 990-202-007 |
| Seal kit - Cartridge | Polyurethane: 990-002-002 |
| Seal kit - Cartridge | Viton: 990-202-006 |

OPTION SELECTION EXAMPLE: LPFCXHN

| CONTROL | (X) DIFFERENTIAL PRESSURE | (H) SEAL MATERIAL | (N) MATERIAL/COATING |
|------------------|---------------------------|-------------------|---------------------------------|
| X Not Adjustable | H 200 psi (14 bar) | N Buna-N | Standard Material/Coating |
| | D 50 psi (3,5 bar) | E EPDM | /AP Stainless Steel, Passivated |
| | F 100 psi (7 bar) | V Viton | /LH Mild Steel, Zinc-Nickel |
| | G 150 psi (10,5 bar) | | |

TECHNICAL FEATURES

- If a higher compensating pressure is needed consider using a direct-acting reducer; PR*R.
- A tuning adjustment (models configured with an L control) is available to vary the pressure drop across the compensator to increase/decrease flow within +/-25% of setting.
- All ports will accept 5000 psi (350 bar).
- Corrosion resistant cartridge valves are intended for use in corrosive environments and are identified by the model code suffix /AP for external stainless steel components, or /LH for external zinc-nickel plated components. See the CONFIGURATION section for all options. For further details, please see the Materials of Construction page located under TECH RESOURCES.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

