



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-17A
Series	3
Capacity	240 L/min.
Maximum Operating Pressure	350 bar
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Model Weight	0,70 kg
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

OPTION SELECTION EXAMPLE: LPHCXFGHN

CONTROL	(X) DIFFERENTIAL PRESSURE	(G) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	G 150 psi (10,5 bar)	N Buna-N	Standard Material/Coating
	F 100 psi (7 bar)	E EPDM	/AP Stainless Steel, Passivated
	H 200 psi (14 bar)	V Viton	/LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

