



Normally open modulating elements without an internal orifice act as a restrictive compensator to maintain a constant pressure drop across an orifice, regardless of variations in upstream or downstream pressure.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

**CONFIGURATION OPTIONS**

**Model Code Example: LPJ CXHN**

CONTROL	(X)	DIFFERENTIAL PRESSURE	(H)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>H</b> 200 psi (14 bar)		<b>N</b> Buna-N		Standard Material/Coating
<b>P</b> External 1/4 NPTF Pilot Port, Port 3 Blocked		<b>D</b> 50 psi (3,5 bar)		<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated
		<b>F</b> 100 psi (7 bar)		<b>V</b> Viton		<b>/LH</b> Mild Steel, Zinc-Nickel
		<b>G</b> 150 psi (10,5 bar)				