



CONFIGURATION

X	Control	Not Adjustable
H	Differential Pressure	200 psi (14 bar)
N	Seal Material	Buna-N
	Material/Coating	

TECHNICAL DATA

NOTE:

		DATA
cavidad	T-11A	
Series	1	
Capacity	60 L/min.	
Maximum Operating Pressure	350 bar	
Valve Hex Size	22,2 mm	
Valve Installation Torque	41 - 47 Nm	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	EPDM: 990-011-014	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	EPDM: 990-011-014	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: LRDCXHN

CONTROL	(X)	DIFFERENTIAL PRESSURE	(H)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
X Not Adjustable		H 200 psi (14 bar)		N Buna-N		/LH Mild Steel, Zinc-Nickel	
		F 100 psi (7 bar)		E EPDM		/AP Stainless Steel, Passivated	
		G 150 psi (10,5 bar)		V Viton		Standard Material/Coating	