



CONFIGURATION

X	Control	Not Adjustable
H	Differential Pressure	200 psi (14 bar)
N	Seal Material	Buna-N
	Material/Coating	

NOTE: DATA MAY VARY BY PART NUMBER. SEE CONFIGURATION SECTION.

TECHNICAL DATA

cavidad	T-2A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

OPTION SELECTION EXAMPLE: LRFCXHN

CONTROL	(X)	DIFFERENTIAL PRESSURE	(H)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
X Not Adjustable		H 200 psi (14 bar)		N Buna-N		/LH Mild Steel, Zinc-Nickel	
		F 100 psi (7 bar)		E EPDM		/AP Stainless Steel, Passivated	
		G 150 psi (10,5 bar)		V Viton		Standard Material/Coating	