



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-2A
	2
	120 L/min.
	350 bar
	3:1
	See Technical Features
	1,7 bar
	0,3 cc/min.
	30 cc/min.
	9
	≥77% of setting
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

# OPTION SELECTION EXAMPLE: MBEALHN

	(L)	(H)	(N)	MATERIAL/COATING
<b>L</b>		<b>H</b> 1000 - 4000 psi (70 - 280 bar), 3000 psi (210 bar)	<b>N</b>	Standard Material/Coating
<b>C</b> -		<b>J</b> 2000 - 5000 psi (140 - 350 bar), 3000 psi (210 bar)	<b>V</b>	/AP /LH

## TECHNICAL FEATURES

- 1.3
- H 3080 psi (212 bar)
- J 3850 psi (265 bar)
- 
- H 1000psi 70bar J 2000psi
- 2 , 1+ x
- 3
- 
- /AP /LH
- 3
- Sun
- 
- 
- Sun

## PERFORMANCE CURVES

