



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-2A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Pilot Ratio	1.5:1
Maximum Recommended Load Pressure	See Technical Features
Adjustment - No. of CCW Turns from Min. to Max. Setting	9
Check Cracking Pressure	1,7 bar
Factory Pressure Settings Established at	30 cc/min.
Maximum Valve Leakage at Reseat	0,3 cc/min.
Reseat	≥77% of setting
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

# OPTION SELECTION EXAMPLE: MBEBLHN

**CONTROL**

- L** Standard Screw Adjustment
- C** Tamper Resistant - Factory Set

**(L) FUNCTIONAL SETTING RANGE**

- H** 1000 - 4000 psi (70 - 280 bar), 3000 psi (210 bar) Standard Setting
- J** 2000 - 5000 psi (140 - 350 bar), 3000 psi (210 bar) Standard Setting

**(H) SEAL MATERIAL**

- N** Buna-N
- V** Viton

**(N)**

## PERFORMANCE CURVES

