



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-2A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Check Cracking Pressure	1,7 bar
Maximum Valve Leakage at Reseat	See Technical Features
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

OPTION SELECTION EXAMPLE: MBEMXGHIN

CONTROL	(X) MINIMUM CONTROL PRESSURE	(G) SEAL MATERIAL	(N)
X Not Adjustable	G 150 psi (10,5 bar)	N Buna-N	
	H 200 psi (14 bar)	V Viton	
	I 300 psi (20 bar)		
	K 450 psi (33 bar)		
	M 525 psi (36,7 bar)		

PERFORMANCE CURVES

