



**CONFIGURATION**

<b>L</b>	
<b>H</b>	1000 - 4000 psi (70 - 280 bar), 3000 psi (210 bar)
<b>N</b>	
	Material/Coating

**TECHNICAL DATA**

NOTE:

	T-17A	DATA
	3	MAY
	240 L/min.	VARY
	350 bar	BY
	1.5:1	
	See Technical Features	
	1,7 bar	
	0,3 cc/min.	
	30 cc/min.	
	9	
	≥77% of setting	
	31,8 mm	
	203 - 217 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
Seal kit - Cartridge	Buna: 990-017-007	
Seal kit - Cartridge	Polyurethane: 990-017-002	
Seal kit - Cartridge	Viton: 990-017-006	

CONFIGURATION. SEE  
CONFIGURATION SECTION.

# OPTION SELECTION EXAMPLE: MBGBLHN

	(L)	(H)	(N)	MATERIAL/COATING
<b>L</b>	<b>H</b>	1000 - 4000 psi (70 - 280 bar), 3000 psi (210 bar)	<b>N</b>	Standard Material/Coating
		<b>J</b> 2000 - 5000 psi (140 - 350 bar), 3000 psi (210 bar)	<b>V</b>	/AP

## TECHNICAL FEATURES

- 1.3
- H 3080 psi (212 bar)
- J 3850 psi (265 bar)
- 
- H 1000psi 70bar J 2000psi
- 2 , 1+ x
- 3
- 
- /AP /LH
- 3
- Sun
- 
- 
- Sun

## PERFORMANCE CURVES

