



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	240 L/min.
	350 bar
	4.5:1
	See Technical Features
	1,7 bar
	0,3 cc/min.
	30 cc/min.
-	9
	≥77% of setting
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

OPTION SELECTION EXAMPLE: MBGGLJN

	(L)	(J)	(N)	MATERIAL/COATING
L		J 2000 - 5000 psi (140 - 350 bar), 3000 psi (210 bar) H 1000 - 4000 psi (70 - 280 bar), 3000 psi (210 bar)	N V	Standard Material/Coating /AP /LH -

TECHNICAL FEATURES

- 1.3
- H 3080 psi (212 bar)
- J 3850 psi (265 bar)
-
- H 1000psi 70bar J 2000psi
- 2 , 1+ x
- 3
-
- /AP /LH
- 3
- Sun
-
-
- Sun

PERFORMANCE CURVES

