



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-17A
Series	3
Capacity	240 L/min.
Maximum Operating Pressure	350 bar
Check Cracking Pressure	1,7 bar
Maximum Valve Leakage at Reseat	See Technical Features
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

# OPTION SELECTION EXAMPLE: MBGMXGIN

CONTROL	(X) MINIMUM CONTROL PRESSURE	(I) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>I</b> 300 psi (20 bar) <b>G</b> 150 psi (10,5 bar) <b>K</b> 450 psi (33 bar) <b>M</b> 525 psi (36,7 bar)	<b>N</b> Buna-N <b>V</b> Viton	Standard Material/Coating <b>/LH</b> Mild Steel, Zinc-Nickel

## PERFORMANCE CURVES

