



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-19A
	4
	480 L/min.
	350 bar
	4.5:1
	See Technical Features
	1,7 bar
	0,3 cc/min.
	30 cc/min.
	7
	≥77% of setting
	41,3 mm
	474 - 508 Nm
	5,5 mm
	19,1 mm
	35 - 40 Nm
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

# OPTION SELECTION EXAMPLE: MBIGLHN

	(L)	(H)	(N)	MATERIAL/COATING
<b>L</b>	<b>H</b>	1000 - 4000 psi (70 - 280 bar), 3000 psi (210 bar)	<b>N</b>	Standard Material/Coating
		<b>J</b> 2000 - 5000 psi (140 - 350 bar), 3000 psi (210 bar)	<b>V</b>	/LH -

## TECHNICAL FEATURES

- 1.3
- H 3080 psi (212 bar)
- J 3850 psi (265 bar)
- 
- H 1000psi 70bar J 2000psi
- 2 , 1+ x
- 3
- 
- /AP /LH
- 3
- Sun
- 
- 
- Sun

## PERFORMANCE CURVES

