



2 1

1 2

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-22A
	2
	120 L/min.
	350 bar
	1,7 bar
	See Technical Features
	28,6 mm
	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

OPTION SELECTION EXAMPLE: MWEMXEGHIN

	(X)	(E)	(N)	MATERIAL/COATING
X	E	75 psi (5 bar)	N	Standard Material/Coating
	G	150 psi (10,5 bar)	V	/AP
	H	200 psi (14 bar)		/LH -
	I	300 psi (20 bar)		
	K	450 psi (33 bar)		
	M	525 psi (36,7 bar)		

TECHNICAL FEATURES

-
- I K M 200psi 14bar 5 / 0.3cc/min E G H 50psi 3.5bar 3 / 5
- E G H
-
- 4
-
-
- Sun
-
- Sun

PERFORMANCE CURVES

