



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-22A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Check Cracking Pressure	1,7 bar
Maximum Valve Leakage at Reseat	See Technical Features
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

OPTION SELECTION EXAMPLE: MWEMXGHIN

CONTROL	(X)	MINIMUM CONTROL PRESSURE	(G)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		G 150 psi (10,5 bar)		N Buna-N		Standard Material/Coating
		H 200 psi (14 bar)		V Viton		/AP Stainless Steel, Passivated
		I 300 psi (20 bar)				/LH Mild Steel, Zinc-Nickel
		K 450 psi (33 bar)				
		M 525 psi (36,7 bar)				

PERFORMANCE CURVES

