


4-Port Vented, Non-adjustable



### CONFIGURATION

L	Factory Set	4000 psi (280 bar)
N	Seal Material	Buna-N

Fixed setting, vented, load reactive load control valves with pilot assist combine two valves; a check valve and a relief valve. The check valve allows free flow from the directional valve (port 2) to the load (port 1) while a direct-acting, pilot-assisted relief valve controls flow from port 1 to port 2. Pilot assist at port 3 lowers the effective setting of the relief valve at a rate determined by the pilot ratio. Backpressure at port 2

does not affect the valve setting because the spring chamber references the vent (port 4).

### TECHNICAL DATA

Maximum Operating Pressure	5000 psi
Pilot Ratio	3:1
Maximum Recommended Load Pressure	See Technical Features
Check Cracking Pressure	25 psi
Factory Pressure Settings Established at	2 in <sup>3</sup> /min.
Maximum Valve Leakage at Reseat	5 drops/min.
Reseat	≥77% of setting
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

### CONFIGURATION OPTIONS

Model Code Example: MWGAXLN

#### FACTORY SET

- L 4000 psi (280 bar)
- K 3000 psi (210 bar)
- M 5000 psi (350 bar)

(L)

#### SEAL MATERIAL

- N Buna-N
- V Viton

(N)