



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-23A
Series	3
Capacity	240 L/min.
Maximum Operating Pressure	350 bar
Pilot Ratio	4.5:1
Maximum Recommended Load Pressure	See Technical Features
Adjustment - No. of CCW Turns from Min. to Max. Setting	9
Check Cracking Pressure	1,7 bar
Factory Pressure Settings Established at	30 cc/min.
Maximum Valve Leakage at Reseat	0,3 cc/min.
Reseat	≥77% of setting
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

OPTION SELECTION EXAMPLE: MWGGLHN

CONTROL

(L)

FUNCTIONAL SETTING RANGE

(H)

SEAL MATERIAL

(N)

L Standard Screw Adjustment

H 1000 - 4000 psi (70 - 280 bar), 3000 psi (210 bar) Standard Setting

N Buna-N

J 2000 - 5000 psi (140 - 350 bar), 3000 psi (210 bar) Standard Setting

V Viton

PERFORMANCE CURVES

