



in. (mm)

2 1

1 2

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-23A
	3
	240 L/min.
	350 bar
	1,7 bar
	See Technical Features
	31,8 mm
	203 - 217 Nm
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

# OPTION SELECTION EXAMPLE: MWGMXGINV

	(X)	(I)	(N)	MATERIAL/COATING
<b>X</b>	<b>I</b>	<b>300 psi (20 bar)</b>	<b>N</b>	Standard Material/Coating
	<b>E</b>	75 psi (5 bar)	<b>V</b>	/AP
	<b>G</b>	150 psi (10,5 bar)		/LH -
	<b>K</b>	450 psi (33 bar)		
	<b>M</b>	525 psi (36,7 bar)		

## TECHNICAL FEATURES

- 
- I K M                    200 psi (14 bar)                    5 drops/min (0,3 cc/min) E G                    50 psi (3,5 bar)                    3 in<sup>3</sup>/min (50 cc/min)
- E G                    0
- 
- 1                    2
- 4
- 
- 
- Sun
- 
- Sun

## PERFORMANCE CURVES

