



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

CONFIGURATION OPTIONS

Model Code Example: NCCBLCN

CONTROL	(L)	ANTI-RETORNO DE CAUDAL INVERSO	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		C 30 psi (2 bar)	N Buna-N		Standard Material/Coating
H Calibrated Handknob with Detent Lock			E EPDM		/AP Stainless Steel, Passivated
K manilla			V Viton		/LH Mild Steel, Zinc-Nickel