



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

CONFIGURATION OPTIONS

Model Code Example: NCCCLCN

CONTROL

(L)

ANTI-RETORNO DE CAUDAL INVERSO

SEAL MATERIAL

(N)

MATERIAL/COATING

L Standard Screw Adjustment

C 30 psi (2 bar)

N Buna-N

Standard Material/Coating

H Calibrated Handknob with Detent Lock

V Viton

/AP Stainless Steel, Passivated

K manilla

/LH Mild Steel, Zinc-Nickel