



2 1

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-13A
	1
	8 L/min. (2,3 mm)
	350 bar
110 SUS (24 cSt)	0,3 cc/min.
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.14 kg.
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

: • O 1 0.75 in. (19 mm)

# OPTION SELECTION EXAMPLE: NCCCLCN

	(L)	(C)	(N)	(N) MATERIAL/COATING
<b>L</b>	<b>C</b> 30 psi (2 bar)	<b>N</b>	Standard Material/Coating	
H	A 4 psi (0,3 bar)	V	/AP	
	B 15 psi (1 bar)		/LH	-
	D 50 psi (3,5 bar)			
	E 75 psi (5 bar)			

## TECHNICAL FEATURES

- 2
- 1 2
- 

## PERFORMANCE CURVES

