



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-13A
	1
	4 L/min. (1,5 mm)
	350 bar
110 SUS (24 cSt)	0,3 cc/min.
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.15 kg.
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

: • 0 1 0.75 in. (19 mm)

# OPTION SELECTION EXAMPLE: NCCDLEN

	(L)	(E)	(N)	MATERIAL/COATING
<b>L</b>	<b>E</b> 75 psi (5 bar)	<b>N</b>	Standard Material/Coating	
H	A 4 psi (0,3 bar)	V	/AP	
O	B 15 psi (1 bar)		/LH -	
	C 30 psi (2 bar)			
	D 50 psi (3,5 bar)			

## TECHNICAL FEATURES

- 2
- 1 2
- 

## PERFORMANCE CURVES

