



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

**CONFIGURATION OPTIONS**

**Model Code Example: NFCDLFN**

CONTROL	(L)	MAXIMUM ORIFICE DIAMETER	(F)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>L</b> Standard Screw Adjustment		<b>F</b> .33 in. (8,4 mm)		<b>N</b> Buna-N		Standard Material/Coating
<b>H</b> Calibrated Handknob with Detent Lock				<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated
<b>K</b> manilla				<b>V</b> Viton		<b>/LH</b> Mild Steel, Zinc-Nickel