



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-5A
Series	2
Capacity	45 L/min. (6,4 mm)
Maximum Operating Pressure	350 bar
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.28 kg.
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Viton: 990-203-006

OPTION SELECTION EXAMPLE: NFDCLAN

CONTROL	(L) MAXIMUM ORIFICE DIAMETER	(A) SEAL MATERIAL	(N) MATERIAL/COATING
L Standard Screw Adjustment	A .25 in. (6,4 mm)	N Buna-N	Standard Material/Coating
H Calibrated Handknob with Detent Lock	B .12 in. (3,0 mm)	E EPDM	/AP Stainless Steel, Passivated
K manilla		V Viton	/LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

