



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---|---------------------------|
| Maximum Operating Pressure | 350 bar |
| Adjustment - No. of CCW Turns from Fully Closed to Fully Open | 5 |
| Locknut Hex Size | 15 mm |
| Locknut Torque | 9 - 10 Nm |
| Seal kit - Cartridge | Buna: 990-203-007 |
| Seal kit - Cartridge | Polyurethane: 990-203-014 |
| Seal kit - Cartridge | Viton: 990-203-006 |
| Seal kit - Cartridge | Buna: 990-203-007 |
| Seal kit - Cartridge | Polyurethane: 990-203-014 |
| Seal kit - Cartridge | Viton: 990-203-006 |

CONFIGURATION OPTIONS

Model Code Example: NFDDLGN

| CONTROL | (L) | MAXIMUM ORIFICE DIAMETER | (G) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|---|-----|---------------------------|-----|-----------------|-----|--|
| L Standard Screw Adjustment | | G .5 in. (12,7 mm) | | N Buna-N | | Standard Material/Coating |
| H Calibrated Handknob with Detent Lock | | | | E EPDM | | /AP Stainless Steel, Passivated |
| K manilla | | | | V Viton | | /LH Mild Steel, Zinc-Nickel |