



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---|---------------------------|
| cavidad | T-5A |
| Series | 2 |
| Capacity | 200 L/min. (12,7 mm) |
| Maximum Operating Pressure | 350 bar |
| Adjustment - No. of CCW Turns from Fully Closed to Fully Open | 5 |
| Valve Hex Size | 28,6 mm |
| Valve Installation Torque | 61 - 68 Nm |
| Adjustment Screw Internal Hex Size | 4 mm |
| Locknut Hex Size | 15 mm |
| Locknut Torque | 9 - 10 Nm |
| Model Weight | 0.28 kg. |
| Seal kit - Cartridge | Buna: 990-203-007 |
| Seal kit - Cartridge | Polyurethane: 990-203-014 |
| Seal kit - Cartridge | Viton: 990-203-006 |
| Seal kit - Cartridge | Buna: 990-203-007 |
| Seal kit - Cartridge | Polyurethane: 990-203-014 |
| Seal kit - Cartridge | Viton: 990-203-006 |

OPTION SELECTION EXAMPLE: NFDDLGN

| CONTROL | (L) MAXIMUM ORIFICE DIAMETER | (G) SEAL MATERIAL | (N) MATERIAL/COATING |
|---|------------------------------|-------------------|--|
| L Standard Screw Adjustment | G .5 in. (12,7 mm) | N Buna-N | Standard Material/Coating |
| H Calibrated Handknob with Detent Lock | | E EPDM | /AP Stainless Steel, Passivated |
| K manilla | | V Viton | /LH Mild Steel, Zinc-Nickel |

PERFORMANCE CURVES

