



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-16A
Series	3
Capacity	120 L/min. (9,7 mm)
Maximum Operating Pressure	350 bar
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.55 kg.
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

## OPTION SELECTION EXAMPLE: NFECLEN

CONTROL	(L) MAXIMUM ORIFICE DIAMETER	(E) SEAL MATERIAL	(N) MATERIAL/COATING
<b>L</b> Standard Screw Adjustment	<b>E</b> .38 in. (9,7 mm)	<b>N</b> Buna-N	Standard Material/Coating
	<b>F</b> .28 in. (7,1 mm)	<b>E</b> EPDM	<b>/AP</b> Stainless Steel, Passivated
		<b>V</b> Viton	<b>/LH</b> Mild Steel, Zinc-Nickel

### PERFORMANCE CURVES

