



针阀为全调型节流口以用来调节流量。它们可在全闭与最大节流口直径之间无限调节。此类阀无压力补偿。它们可以用来做流量控制或者截止阀。

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| 最大操作压力 | 350 bar |
| 调节 - 从全关到全开的逆时针圈数 | 5 |
| 锁紧螺母六角尺寸 | 15 mm |
| 锁紧螺母力矩 | 9 - 10 Nm |
| Seal kit - Cartridge | Buna: 990-016-007 |
| Seal kit - Cartridge | EPDM: 990-016-014 |
| Seal kit - Cartridge | Polyurethane: 990-016-002 |
| Seal kit - Cartridge | Viton: 990-016-006 |

CONFIGURATION OPTIONS

Model Code Example: NFEDLHN

| 控制方式 | (L) 最大节流孔直径 | (H) 密封材料 | (N) MATERIAL/COATING |
|---------------------|----------------------------|---------------|---------------------------|
| L 标准螺钉调节 | H .69 in. (17,5 mm) | N 丁腈橡胶 | Standard Material/Coating |
| H 刻度旋钮, 带止动锁 | | E EPDM | /AP 不锈钢, 钝化 |
| Y 三爪旋钮 | | V 氟橡胶 | /LH 低碳钢, 锌-镍 |