



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006

**CONFIGURATION OPTIONS**

**Model Code Example: NFFCLGN**

CONTROL	(L)	MAXIMUM ORIFICE DIAMETER	(G)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>L</b> Standard Screw Adjustment		<b>G</b> .56 in. (14,2 mm)		<b>N</b> Buna-N		Standard Material/Coating
<b>H</b> Calibrated Handknob with Detent Lock		<b>H</b> .38 in. (9,7 mm)		<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated
<b>K</b> manilla				<b>V</b> Viton		<b>/LH</b> Mild Steel, Zinc-Nickel