



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-163A
	0
	20 L/min.
	350 bar
	blocked control port (dead headed)
	0,11 - 0,16 L/min.
	5
	19,1 mm
	27 - 33 Nm
	4 mm
	12,7 mm
	9 - 10 Nm
	0.11 kg.
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006

OPTION SELECTION EXAMPLE: PBBBLAN

	(L)	(A)	(N)	MATERIAL/COATING
L	A	75 - 3000 psi (5 - 210 bar), 200 psi (14 bar)	N	Standard Material/Coating
W	B	75 - 1500 psi (5 - 105 bar), 200 psi (14 bar)	E	/AP
	N	75 - 800 psi (5 - 55 bar), 200 psi (14 bar)	V	/LH
	Q	75 - 400 psi (5 - 28 bar), 200 psi (14 bar)		
	W	75 - 4500 psi (5 - 315 bar), 200 psi (14 bar)		

TECHNICAL FEATURES

- 1 2
- 75 psi (5 bar)
- /
- 3 1:1 5000 psi 350 bar
- Sun /
- A,B,N,Q 3000 psi (210 bar) W 5000 psi (350 bar)

PERFORMANCE CURVES

