



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|------------------------------------|
| | 350 bar |
| | blocked control port (dead headed) |
| | 0,11 - 0,16 L/min. |
| - | 5 |
| | 15 mm |
| | 9 - 10 Nm |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | EPDM: 990-011-014 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |

: • : A B 3000 psi (210 bar) N Q 2000 psi (140 bar) W 5000 psi (350 bar)
• O 1 0.75 in. (19 mm)

CONFIGURATION OPTIONS

Model Code Example: PBDBLAN

| (L) | (A) | (N) | MATERIAL/COATING |
|----------|---|----------|---------------------------|
| L | A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) | N | Standard Material/Coating |
| C | B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) | V | /AP |
| K | D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) | | /LH |
| Y | E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) | | |
| | G 60 - 3000 psi (4 - 210 bar), 200 psi (14 bar) | | |
| | K 75 - 1500 psi (5 - 105 bar), 200 psi (14 bar) | | |
| | N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) | | |
| | P 40 - 400 psi (2,8 - 28 bar), 200 psi (14 bar) | | |
| | Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) | | |
| | W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) | | |