



**CONFIGURATION**

L	
A	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)
N	
Material/Coating	

**TECHNICAL DATA**

NOTE:  
DATA  
MAY  
VARY  
BY

	T-11A
	1
	40 L/min.
	350 bar
	blocked control port (dead headed)
	0,11 - 0,16 L/min.
	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.16 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

CONFIGURATION. SEE  
CONFIGURATION SECTION.

: • : A B 3000 psi (210 bar) N Q 2000 psi (140 bar) W 5000 psi (350 bar)  
• O 1 0.75 in. (19 mm)

# OPTION SELECTION EXAMPLE: PBDBLAN

	(L)	(A)	(N)	MATERIAL/COATING	(/LH)
<b>L</b>	-	A	N	/LH	-
<b>C</b>	-	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	V	/AP	
<b>K</b>		B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)			Standard Material/Coating
<b>W</b>		N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)			
<b>Y</b>		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			
		W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)			

## TECHNICAL FEATURES

- 3 / 3
- 1 2
- /
- 150
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 3 1:1 5000 psi 350 bar
- /
- W Y W Y
- EPDM
- /AP
- Sun /

## PERFORMANCE CURVES

